


NEW CONDENSING HEATERS



- **PVC Venting**
 - Zero clearance to combustible
 - 3" or 4" PVC
- **Stainless Steel Heat Exchanger**
 - Residual heat used to pre-heat incoming water
 - Durable & high strength
 - Corrosion resistant
- **Copper Heat Exchanger**
 - Commercial grade copper
 - 25% thicker piping
 - Unique efficient heat distribution design
- **Temperature Settings from 100°F-180°F**
- **Neutralizer Included**

CONDENSING 93.3% Efficient TECHNOLOGY

NORITZ RESIDENTIAL

841 series

841 SERIES MODELS Specification Chart

Flow Rates*

Summer/
Water Supply 70°F

4.1
Showers



Winter/
Water Supply 45°F

2.5
Showers



Specification	N-0841MC (Stainless Steel)	N-0841MC-DV (Stainless Steel)
	Max: 199,900 btuh Min: 11,000 btuh <ul style="list-style-type: none"> ▶ Turbo Flow Up to 11.1 GPM ▶ Quick-Connect ▶ Multi-system (up to 24 units) ▶ 3" or 4" PVC or stainless venting 	Max: 199,900 btuh Min: 11,000 btuh <ul style="list-style-type: none"> ▶ Turbo Flow Up to 11.1 GPM ▶ Quick-Connect ▶ Multi-system (up to 24 units) ▶ 3" or 4" PVC or stainless venting
Item		
Gas Consumption	NG/ Efficiency Max. 199,900 btuh- Min. 11,000 btuh/ 93.3%	Max. 199,900 btuh- Min. 11,000 btuh/ 93.3%
	LP/ Efficiency Max. 199,900 btuh- Min. 11,000 btuh/ 93.4%	Max. 199,900 btuh- Min. 11,000 btuh/ 93.4%
Capacity Range	0.5-11.1 Gal/min.	0.5-11.1 Gal/min.
Dimensions	24.2"(Height) x 18.3"(Width) x 9.4"(Depth)	24.4"(Height) x 18.4"(Width) x 9.4"(Depth)
Included Accessories	Remote Controller, Remote Controller Cord, Anchoring Screws, Condensate Neutralizer	
MSRP	\$2,399.00	\$2,399.00

NEW CONCENTRIC VENTED HEATERS



All Stainless Concentric Venting

- 5" Outer & 3" Inner Diameter
- Zero Clearance Venting
- Single Wall Penetration

Flexible Installation Options

- Adjustable venting
- Perfect for space and/ or air constrained indoor locations.

Built-in Remote

Commercial Grade Heat Exchanger

- Dual Flame Burner
- Resin Coated PC Board
- 9.8 GPM Turbo Flow
- Quick Connect-Link 2 Heaters



NORITZ RESIDENTIAL

751 series

N-0751M-DVC Specification Chart

Flow Rates*

Summer/
Water Supply 70°F

3.9
Showers



Winter/
Water Supply 45°F

2.2
Showers



Specification	N-0751M-DVC
	Indoor Concentric Max: 199,900 btuh Min: 11,000 btuh <ul style="list-style-type: none"> ▶ Turbo Flow Up to 9.8 GPM ▶ Quick-Connect ▶ Concentric Venting (5" Outer/3" Inner Diameter)
Item	
Gas Consumption	NG/ Efficiency Max. 199,900 btuh- Min. 11,000 btuh/ 84%
	LP/ Efficiency Max. 199,900 btuh- Min. 11,000 btuh/ 84%
Capacity Range	0.5-9.8 Gal/min.
Dimensions	23.6"(Height) x 13.8"(Width) x 10.2"(Depth)
Included Accessories	Anchoring Screws, Built-in Remote
MSRP	\$1,399.00 US